


Starting with some routing incidents...



- A Prefix is announced by both AS 134599 and AS 133957 (might be unintentional)
- Either AS cloud be closest to different geographic locations
- Legitimate traffic might get blackholed

	Announced E	Зу
Origin AS	Announcemen	nt
AS134599	45.118.70.0/24	<b>~</b>
AS133957	45.118.70.0/24	<b>✓</b>

route-views>show ip bgp 45.118.70.0/24 | i 133957
3277 3267 174 58601 138197 138197 138197 138197 138197 133957
24441 3491 3491 3257 58601 138197 138197 138197 138197 138197 138957
3561 209 174 58601 138197 138197 138197 138197 138197 133957
20912 174 58601 138197 138197 138197 138197 138197 133957
852 174 58601 138197 138197 138197 138197 138197 133957
101 101 174 58601 138197 138197 138197 138197 138197 133957
3267 174 58601 138197 138197 138197 138197 138197 133957
3303 3257 58601 138197 138197 138197 138197 138197 138197 138957
54728 20130 23352 3257 58601 138197 138197 138197 138197 138197 138197 138197 138197

8283 6762 132602 58717 135341 135341 135341 135341 134599

- Issue informed to the IP owner.
- They removed one announcement
- Created ROA for valid ASN
- Valid announcement visible in the global routing table


	Announced By
Origin AS	Announcement
AS133957	45.118.70.0/24


route-views>show ip bgp 45.118.70.0/24 | 1 133957 3277 3267 174 58601 138197 138197 138197 138197 138197 133957 24441 3491 3491 3257 58601 138197 138197 138197 138197 138957 3561 209 174 58601 138197 138197 138197 138197 138197 133957 20912 174 58601 138197 138197 138197 138197 138197 133957 852 174 58601 138197 138197 138197 138197 138197 133957 101 101 174 58601 138197 138197 138197 138197 138197 133957 3267 174 58601 138197 138197 138197 138197 138197 133957 3303 3257 58601 138197 138197 138197 138197 138197 133957

route-views>sho ip bgp 45.118.70.0/24 | i 134599 route-views>

- Client AS didn't update APNIC membership
- Shouldn't have valid prefix allocation with revoked membership
- Transit still announces client's prefixes
- Prefixes marked as BOGON in global routing table








- The issue has been informed to the transit provider
- Then, they dropped it
- The announcement was removed from global table

 Later on, the AS got membership renewed and has its allocated prefixes back for use

route-views>show	ip bgp	103.92.152.0/24
% Network not in	table	
route-views>show	ip bgp	103.92.153.0/24
% Network not in	table	
route-views>show	ip bgp	103.92.154.0/24
% Network not in	table	
route-views>show	ip bgp	103.92.155.0/24
% Network not in	table	


Prefix	
103.67.199.0/24	BK ONLINE
103.92.152.0/24	BK ONLINE
103.92.153.0/24	BK ONLINE
103.92.154.0/24	BK ONLINE
103.92.155.0/24	BK ONLINE

- AS 64075 delegated its prefix 103.204.210.0/24 to AS 137842
- AS 137842 announced the prefix
- AS 64075 is also announcing its delegated prefixes as AS 137842 (AS Hijack)
- It's upstream accepting it and further announcing it globally



#### **AS137842 MH ONLINE**

Entry cached for another 60 seconds.




				core1.sin1.he	.net	> show	ip bgp r	outes de	tail 202.181.16.0/24			
Matching Routes	10											
Status Codes		gregate <b>B</b> - Best <b>b</b> - N ssed <b>F</b> - Filtered <b>s</b> - S			ratior	eBGP <b>D</b>	Damped I	E - eBGP H	- History I - iBGP L - Local M - Multipath m - Not	: Installed M	ultipath <b>S</b>	-
Statu	s \$	Network	<b>\$</b>	Next Hop	<b>\$</b>	Metri⇔	LocPr₽	Weight	Path	<b>\$</b>	Origin≑	ROA*
BEx		202.181.16.0/24		74.82.51.74		0	140	0	132602, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		27.111.228.140		0	100	0	10075, 134371, 137842		IGP	0
E		202.181.16.0/24		27.111.228.140		0	100	0	9975, 134371, 137842		IGP	0
E		202.181.16.0/24		27.111.228.140		0	100	0	10075, 134371, 137612		IGP	0
E		202.181.16.0/24		27.111.228.40		0	100	0	9498, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		27.111.229.76		0	100	0	132602, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		65.49.109.182		0	100	0	9498, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		27.111.228.111		0	100	0	6762, 132602, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		74.82.48.70		0	100	0	3491, 9498, 10075, 134371, 137842		IGP	0
E		202.181.16.0/24		216.218.221.142		0	100	0	4637, 9498, 10075, 134371, 137842		IGP	0
Last Up	date	4d5h31m58s ago (1	path	installed)								

#SANOG35

2019-00-24 13:20:23 UTC


- A /64 IPv6 prefix announced in global routing table
- Most specific announcement in global table is /48
- A /64 should never be in global routing table



- The issue was informed to the AS
- The announcement has been removed

Prefix	
2405:1500::/32	<b>Q</b> 🗸
2405:1500::/48	<b>Q</b> 🗸
2405:1500:30::/48	<b>Q</b> 🗸
2405:1500:40::/48	<b>Q</b> 🗸
2405:1500:60::/48	<b>Q</b> 🗸
2405:1500:70::/48	<b>Q</b> 🗸
2405:1500:80::/48	<b>Q</b>

Somebody is announcing non-routable prefixes in the global BGP table.





Prefix	
103.82.232.0/24	<b>Q</b>
103.96.230.0/23	<b>Q Z</b>
103.96.232.0/24	2
123.253.228.0/22	20

The announcement has been removed once the issue was informed to them

- Previously, AS 136909 used transit from AS 24342 using static routing.
- AS 24342 announced prefixes of AS 136909 in global BGP table on their behalf.

 Later, AS 136909 stated doing BGP but AS 24342 still didn't stop the announcement.





- AS 24342 has been informed to stop announcing client's prefixes
- Client AS 136909 has signed their prefixes
- Issue resolved.

route-views>show ip bgp 103.98.200.0/24 | i 24342 7660 2516 6453 58601 24342 24 342 24342 136909 286 6453 58601 24342 24342 24 342 136909 852 3491 9498 58601 24342 24 342 24342 136909 6079 4637 9498 58601 24342 24 342 24342 136909 1351 9498 58601 24342 24342 2 4342 136909 54728 20130 6939 58601 24342 24342 24342 136909 3333 1257 6453 58601 24342 24 342 24342 136909 3267 6461 7473 17494 58601 24342 24342 136909 1403 6453 58601 24342 24342 136909 1403 6453 58601 24342 24342 136909 8283 6453 58601 24342 24342 136909 57866 6461 7473 17494 58601 24342 24342 136909 57866 6461 7473 17494 58601 24342 24342 136909 3277 3267 6461 7473 17494 58601 24342 24342 136909 3277 3267 6461 7473 17494 58601 24342 24342 136909 3277 3267 6461 7473 17494 58601 24342 24342 136909

AS Info Graph v4 Prefixes v4	Peers v4
Prefix	
103.98.200.0/22	<b>Q</b> 🗸
103.98.200.0/24	2
103.98.201.0/24	2
103.98.202.0/24	2
103.98.203.0/24	<b>Q</b> 🗸

L				
			Prefix	
	115.127.	0.0/17		<b>Q</b>
	115.127.	0.0/18		<b>Q</b>
	115.127.	0.0/19		<b>Q</b>
	115.127.	0.0/20		<b>Q</b> 🗸
	115.127.	0.0/24		<b>Q</b>
	115.127.	1.0/24		<b>Q</b> 🗸
	115.127.	2.0/24		<b>Q</b> 🗸
	115.127.	3.0/24		<b>Q</b> 🗸
	115 127	4 0/24		0

AS Info Graph v4 Prefixes v4 Peers v4

- AS 136901 got an allocation of /22.
- They announce part of its prefix (not the whole), e.g. /23 is announced but the other /23 is not.
- Opportunists can try to use the unannounced /23 for unauthorized activities.


Prefix	
103.98.64.0/24	V
103.98.65.0/24	<b>/</b>

awal@Awals-MacBook-Air ~> whois -h whois.radb.net 103.98.64.0/22

route: 103.98.64.0/22

origin: AS136901

- AS 137515 announced BCC's prefix 103.48.17.0/24 in a NIX (Prefix hijack)
- Important government services became unavailable to the citizens
- Costs our time to fix.



### What they reply about it? Funny but they really did

- We mistakenly announced the prefix
- We do not manually check our clients' APNIC membership status
- The client is very close to us and well trustworthy, so we never required to check their announcements
- We don't do prefix or AS filtering for our clients
- Forgot to stop announcing the prefix after it's delegated to another AS



Image source: Internet

How we ensure the routing hygiene manually?

Nightmare...






image source: internet



Signing prefixes a.k.a. creating ROAs



Route J=	Origin AS	ROA status 😉	Whois status 😉
103.48.16.0/22	AS63932	0	<b>⊘</b>
2401:ED80::/32	AS63932	0	<b>⊘</b>
43.229.12.0/22	AS63932	0	<b>⊘</b>
43.229.15.0/24	AS63932	0	0



Validating ROAs

a.k.a Route Origin Validation

```
RPKI server is 172.20.22.4, port 3323
RPKI current state: Established, Age: 01m46s
  Local host: 172.19.19.1, Local port: 60462
  Remote host: 172.20.22.4, Remote port: 3323
Refresh time: 900
Aging time: 1800
Session ID : 59791
Serial number : 10
Session Statistics:
  IPv4 record : 98101
  IPv6 record : 16506
```

```
RPKI validation codes: V - valid, I - invalid, N - not-found
Total Number of Routes: 1005452
       Network
                                                                               PrefVal Path/Ogn
                          NextHop
                                                                     LocPrf
     V 1.0.0.0/24
                           103.9.114.161
                                                                                 Θ
                                                                                         17806 17494 6453 133351
                           114.130.31.5
    N 1.0.4.0/22
                           103.9.114.161
                           103.9.114.161
                           103.9.114.161
                           103.9.114.161
                                                                                         58601 4826 38803 56203i
                           103.9.114.161
                                                                                         58601 4826 38803 56203i
                           103.9.114.161
                                                                                         58601 2914 2519i
       1.0.16.0/24
     N 1.0.64.0/18
                           103.9.114.161
                                                                                         58601 6453 2497 7670 18144
```



### Why Create ROA?



To ensure the authenticity of your IP resources and help others verify it if requires

	Announced By
Origin AS	Announcement
AS134599	45.118.70.0/24
AS133957	45.118.70.0/24

So that your IP resources are not knowingly or unknowingly used or abused by anyone

# Why Deploy ROV?



To build and maintain a secure and trustworthy global routing infrastructure



To validate BGP routes and identify the authorized originator of the prefix

Image source: Internet


24


# RPKI Validation in NDC and subsequent impact

### RPKI Validation at National Data Center

- NDC declared to drop invalids since Dec 1, 2019
- Bangladesh has more than 700 active ASN
- BD ROA stats in Sep 2019:
  - Valid 29%
  - Unknown 69%
  - Invalid 2%
- Need to find out ASNs who are getting impact
  - BD ASNs are easy to reach for obvious reason
  - How about the global ASNs?

### Awareness Before the ROV





Subject: NDC starts RPKI Validation on Dec 1 Date: Thu, 7 Nov 2019 00:44:32 +0600 From: Md. Abdul Awal <awal.ece@gmail.com>

To:nog <nog@bdnog.org>

Dear Colleagues,

National Data Center (NDC) at Bangladesh Computer Council (BCC) starts RPKI ROA validation on December 1, 2019.

#### Read more here:

https://www.cirt.gov.bd/%e0%a6%9c%e0%a6%be%e0%a6%a4%e0%a7%80%e0%a7 %a6%b8%e0%a7%87%e0%a6%a8%e0%a7%8d%e0%a6%9f%e0%a6%be%e0%a6%b0%

NDC team tried to reach ASNs who have INVALID ROAs and helped many of them to fix it. However, there are still about 2% invalid prefixes in Bangladesh. Please be informed that the INVALID prefixes would not be able to access any content hosted at NDC after Nov 30.

Please spend some time to check the ROA for your prefixes. Correct any invalid ROAs immediately from your MyAPNIC portal. Also, if you didn't create ROA for your prefixes yet, please do so asap.

Best regards, Awal

### Awareness Before the ROV

- We helped others to create and/or fix their ROAs
  - LEAs, Police, Special forces
  - Govt. Organizations
  - IXPs
  - Banks and Financial Organizations
  - Transit providers
  - ISPs
  - Data Centers

Prefix	
123.49.0.0/18	9 🗸
123.49.14.0/24	<b>2</b>
123.49.16.0/20	<b>Q</b>
123.49.29.0/24	
123.49.30.0/24	<b>2</b>
123.49.31.0/24	
123.49.47.0/24	<b>2</b>
180.211.128.0/17	<b>S</b>
180.211.201.0/24	
180.211.214.0/24	<b>2</b>
180.211.215.0/24	
203.112.192.0/19	
203.112.194.0/24	<b>S</b>
209.58.24.0/24	




Prefix	
123.49.0.0/18	<b>S</b>
123.49.14.0/24	<b>S</b>
123.49.16.0/20	2
123.49.29.0/24	2
123.49.30.0/24	<b>Q</b>
123.49.31.0/24	2
123.49.47.0/24	2
180.211.128.0/17	<b>S</b>
180.211.201.0/24	9 🗸
180.211.214.0/24	9 /
180.211.215.0/24	9
203.112.192.0/19	2
203.112.194.0/24	9 🗸


Source: https://bgp.he.net


AS Info	Graph v4	Prefixes v4	Peers v
	D,	efix	
	г	CIIX	
43.255.	20.0/22		<b>9</b>
43.255.	20.0/24		<b>Q</b>
43.255.	21.0/24		<b>Q</b>
43.255.	22.0/24		<b>S</b>
103.239	9.4.0/22		<b>9</b>
103.239	9.4.0/24		<b>9</b>
103.239	9.5.0/24		<b>9</b>
103.239	9.6.0/24		<b>9</b>
103.239	9.7.0/24		<b>Q</b>



AS Info Graph v4 Pref	ixes v4 Peers v
Prefix	
43.255.20.0/24	<b>S</b>
43.255.21.0/24	<b>S</b>
43.255.22.0/24	<b>S</b>
103.239.4.0/24	<b>S</b>
103.239.5.0/24	<b>S</b>
103.239.6.0/24	<b>S</b> 🗸









Nov 2019


Dec 2019

Source: https://observatory.manrs.org










### And, finally NDC drops invalids since Dec 1, 2020



### More organizations to start ROV

- BdREN (AS 63961) Jan, 2020
- Summit Communications (AS 58717) Jan 2019
- BD Link (AS 58668) Jan, 2020
- Link3 Technologies (AS 23688) TBD
- Cybergate (AS 58599) TBD

### How about South Asia and Pakistan?

#### RPKI Status in South Asia




Source: https://observatory.manrs.org


#### RPKI Status in Pakistan



Source: https://observatory.manrs.org

### RPKI Status in Pakistan






- Pakistan has about 1 % INVALID ROAs
  - We need to eliminate it completely
- 79% UNKNOWN That's big
  - Please sign the unsigned!

And, think about doing Route Origin Validation (ROV)


#### Considerations about ROA and ROV

### Creating ROA





- Not a good idea to create ROAs up to /24 if not announced in BGP
- Better to create ROAs for specific prefixes that are announced in BGP



# Creating ROA

Route	Origin AS	ROA status 😉	Whois status <b>6</b>
103.48.16.0/22	AS63932	0	<b>⊘</b>
2401:ED80::/32	AS63932	0	0
43.229.12.0/22	AS63932	0	<b>⊘</b>
43.229.15.0/24	AS63932	0	<b>⊘</b>



Route Ji	Origin AS	ROA status 🕄	Whois status 😉
103.48.16.0/22 +	AS63932	<b>⊘</b>	<b>⊘</b>
2401:ED80::/32 +	AS63932	0	0
43.229.12.0/22 +	AS63932	0	<b>⊘</b>

<code>awal@Awals-MacBook-Air</code> $\sim\!\!\!>$ $whois$ -h whois.bgpmon.net "roa 63932 103.48.16.0/22 0 - Valid		
ROA Details		
	AS63932 2019-12-06 18:22:35 2021-01-31 00:00:00 Expires in 1y55d2h39m25.6000000014901s rpki.apnic.net 103.48.16.0/22 (max length /22) 43.229.12.0/22 (max length /22) 2401:ed80::/32 (max length /32) 43.229.15.0/24 (max length /24)	


## Creating ROA

```
awal@Awals-MacBook-Air ~> whois -h whois.bapmon.net " --roa 17494 103.110.212.0/22"

    Valid

ROA Details
Origin ASN:
                  AS17494
Not valid Before: 2019-11-12 05:41:59
Not valid After: 2020-10-31 00:00:00 Expires in 323d5h27m43s
Trust Anchor:
                  rpki.apnic.net
Prefixes:
                  2407:5000:88::/48 (max length /48)
                  203.112.192.0/19 (max length /24)
                  2407:5000::/32 (max length /40)
                  103.110.212.0/22 (max length /24)
                  123.49.0.0/18 (max length /24)
                  180.211.128.0/17 (max length /24)
awal@Awals-MacBook-Air ~> whois -h whois.bapmon.net " --roa 45588 103.110.212.0/22
 - Not Valid: Invalid Origin ASN, expected 17494
```

You may sign same prefix with multiple ASNs but do if you really really have to



## Doing ROV

```
Network
                      NextHop
I 45.123.40.0/23
                      103.125.54.54
  103.63.158.0/23
                      103.125.54.54
  103.73.104.0/22
                      103.125.54.73
  103.73.105.0/24
                      103.125.54.73
 103.73.106.0/24
                      103.125.54.73
I 103.73.107.0/24
                      103.125.54.73
I 103.87.249.0/24
                      103.125.54.54
I 103.88.234.0/24
                      103.125.54.54
                      103.125.54.53
I 103.114.39.0/24
I 103.121.60.0/24
                      103.125.54.54
I 103.123.168.0/24
                      103.125.54.54
I 103.123.169.0/24
                      103.125.54.54
I 103.126.20.0/22
                      103.125.54.54
I 103.126.20.0/23
                      103.125.54.54
I 103.126.22.0/23
                      103.125.54.54
I 103.130.114.0/24
                      103.125.54.54
I 103.133.201.0/24
                      103.125.54.73
I 103.134.56.0/24
                      103.125.54.54
I 103.134.57.0/24
                      103.125.54.54
```

Validation with allowing invalids for BGP best path selection



```
Network
                      NextHop
  45.123.40.0/23
                      103.125.54.54
  103.63.158.0/23
                      103.125.54.54
  103.73.104.0/22
                      103.125.54.73
  103.73.105.0/24
                      103.125.54.73
  103.73.106.0/24
                      103.125.54.73
I 103.73.107.0/24
                      103.125.54.73
I 103.87.249.0/24
                      103.125.54.54
I 103.88.234.0/24
                      103.125.54.54
I 103.114.39.0/24
                      103.125.54.53
 103.121.60.0/24
                      103.125.54.54
                      103.125.54.54
I 103.123.168.0/24
  103.123.169.0/24
                      103.125.54.54
I 103.126.20.0/22
                      103.125.54.54
I 103.126.20.0/23
                      103.125.54.54
  103.126.22.0/23
                      103.125.54.54
I 103.130.114.0/24
                      103.125.54.54
 103.133.201.0/24
                      103.125.54.73
I 103.134.56.0/24
                      103.125.54.54
I 103.134.57.0/24
                      103.125.54.54
```

Validation without allowing invalids for BGP best path selection

## ROA for Small ISPs and Enterprises

- Have own Internet resources?
  - Creating ROA is straightforward using RIR's resource management portal
- Got assignment for LIR?
  - Have public ASN?
    - Ask the LIR to create ROA with your ASN and verify
  - Don't have public ASN?
    - Ask the LIR to create ROA for the assigned prefix and verify

## ROV for Small ISPs and Enterprises


- Have BGP with transits and peers?
  - Receive full routes from neighbors?
    - Implementing ROV using validator cache is straightforward
  - Receive partial routes with default from neighbors?
    - Ask transits to do ROV for you
    - And, implement ROV using validator cache to validate peer and IX routes
  - Receive default route only
    - ROV wouldn't fit, however, you may ask transits to do ROV in their routers ©
- Have static routing with transits?
  - ROV wouldn't fit, however, you may ask transits to do ROV in their routers ©

# Still thinking why we need ROA and ROV?

- Check the issues discussed in first couple slides
- Reduce the opportunity of routing incidents, prefix hijacks, route leaks, DDoS, outages
- You wouldn't want to be a target of those incidents
- Help improve global routing infrastructure security
- Help each other to maintain routing hygiene
- We are engineers working hard to make Internet better, remember?

# We all can help improve global routing security

- Create/fix ROAs for your prefixes
- If you are a transit provider, ask you clients to do the same
- If you're receiving BGP full route, implement ROV
- Share this among other colleagues in the community
- Help others fix their ROAs



# Let's check your own ASN

Go to <a href="https://bgp.he.net">https://bgp.he.net</a>, search for your
 AS number and check v4 and v6 prefixes


Or,


• Use whois on unix terminal:

whois -h whois.bgpmon.net " --roa ASN Prefix"

• If you find issues with ROA, please fix it

https://blog.apnic.net/2019/09/11/how-to-creating-rpki-roas-in-myapnic/





#### References

- 1. <a href="https://learn.nsrc.org/bgp/MANRS4">https://learn.nsrc.org/bgp/MANRS4</a> RPKI and ROA
- 2. <a href="https://nsrc.org/workshops/2019/mnnog1/riso/networking/routing-security/en/presentations/BGP-Origin-Validation.pdf">https://nsrc.org/workshops/2019/mnnog1/riso/networking/routing-security/en/presentations/BGP-Origin-Validation.pdf</a>
- 3. https://www.manrs.org/manrs
- 4. <a href="https://blog.cloudflare.com/rpki-details/">https://blog.cloudflare.com/rpki-details/</a>
- 5. <a href="https://www.apnic.net/get-ip/faqs/rpki/">https://www.apnic.net/get-ip/faqs/rpki/</a>
- 6. <a href="https://www.apnic.net/community/security/resource-certification/">https://www.apnic.net/community/security/resource-certification/</a>
- 7. <a href="https://blog.apnic.net/2019/10/28/how-to-installing-an-rpki-validator/">https://blog.apnic.net/2019/10/28/how-to-installing-an-rpki-validator/</a>
- 8. <a href="https://blog.apnic.net/2019/09/11/how-to-creating-rpki-roas-in-myapnic/">https://blog.apnic.net/2019/09/11/how-to-creating-rpki-roas-in-myapnic/</a>
- 9. <a href="https://www.apnic.net/wp-content/uploads/2017/12/ROUTE MANAGEMENT GUIDE.pdf">https://www.apnic.net/wp-content/uploads/2017/12/ROUTE MANAGEMENT GUIDE.pdf</a>
- 10. https://www.cirt.gov.bd/জাতীয়-ডাটা-সেন্টারে-আরপি/

# Questions?